



THE SAFE PREPARATION OF GAS MIXTURES

AIGA 047/08

Globally Harmonised Document

Asia Industrial Gases Association

298 Tiong Bahru Road, #20-01 Central Plaza, Singapore 168730

Tel : +65 6276 0160 • Fax : +65 6274 9379

Internet : <http://www.asiaiga.org>



THE SAFE PREPARATION OF GAS MIXTURES

Disclaimer

All publications of AIGA or bearing AIGA's name contain information, including Codes of Practice, safety procedures and other technical information that were obtained from sources believed by AIGA to be reliable and/ or based on technical information and experience currently available from members of AIGA and others at the date of the publication. As such, we do not make any representation or warranty nor accept any liability as to the accuracy, completeness or correctness of the information contained in these publications.

While AIGA recommends that its members refer to or use its publications, such reference to or use thereof by its members or third parties is purely voluntary and not binding.

AIGA or its members make no guarantee of the results and assume no liability or responsibility in connection with the reference to or use of information or suggestions contained in AIGA's publications.

AIGA has no control whatsoever as regards, performance or non performance, misinterpretation, proper or improper use of any information or suggestions contained in AIGA's publications by any person or entity (including AIGA members) and AIGA expressly disclaims any liability in connection thereto.

AIGA's publications are subject to periodic review and users are cautioned to obtain the latest edition.

**ATTENTION IS DRAWN TO THE NEED TO COMPLY WITH
ALL NATIONAL REGULATIONS WHICH AFFECT
THE PREPARATION OF GAS MIXTURES**

Acknowledgement

This document is adopted from the European Industrial Gases Association document IGC 39/08 E 'The safe preparation of gas mixtures'. Acknowledgement and thanks are hereby given to EIGA for permission granted for the use of their document.

Table of Contents

1	Introduction	1
2	Scope and Purpose.....	1
3	Definitions	1
4	Principles of safe gas mixing	2
4.1	Principle 1: written instructions shall be provided	2
4.2	Principle 2: equipment and facilities shall be properly designed	2
4.3	Principle 3: written instructions shall be prepared by competent staff using recognised data	2
4.4	Principle 4: personnel shall be trained.....	2
4.5	Principle 5: intended cylinder-content shall be identified before filling	2
4.6	Principle 6: supply gases and cylinders shall be controlled	2
4.7	Principle 7: facilities and procedures shall be audited	3
5	Feasibility and classification of gas mixtures	3
5.1	Gas mixture availability constraints	3
5.2	Gas mixture categories	3
6	Gas mixing instructions	3
6.1	General controls.....	3
6.2	Mixture-specific manufacturing instructions.....	3
6.3	Personnel responsible for preparing & authorising gas mixing instructions	4
6.4	Safety system.....	4
6.5	Approval of gas mixing instructions	4
6.6	Adjustment of gas mixing instructions	4
6.7	Adjustment of existing mixtures.....	4
6.8	Consideration of mixing methods	5
6.8.1	Static methods	5
6.8.2	Dynamic method	5
6.9	Compatibility considerations.....	5
6.9.1	Cylinders and cylinder valves.....	5
6.9.2	Mixture components.....	6
6.9.3	Safety margins	6
6.10	Identification and labelling	6
7	Design & operation of gas mixing facilities	7
7.1	General requirements	7
7.2	Specific requirements.....	8
7.2.1	Incoming cylinder reception & inspection	8
7.2.2	Disposal of residual gases	8
7.2.3	Cylinder maintenance & preparation	8
7.2.4	Design of gas mixing facilities	9
7.2.5	Operation of gas mixture filling facilities	10
7.2.6	Gas analysis	10
8	Personnel training	10
8.1	All personnel	10
8.2	Cylinder reception/receiving personnel	11
8.3	Gas disposal personnel.....	11
8.4	Cylinder maintenance personnel.....	11
8.5	Cylinder filling personnel	11
8.6	Gas analysis personnel	12
8.7	Cylinder shipping personnel	12
8.8	Plant maintenance personnel.....	12
8.9	Personnel engaged in preparing operating procedures and gas mixing instructions	12
8.10	Personnel engaged in plant and equipment design	13
8.11	Other personnel.....	13

8.12	First-aid training	13
9	Safety	13
9.1	Provision of personal protective equipment.....	13
9.2	Safety rules	14
9.3	Emergency planning	14
9.4	Audits.....	15
Appendix A: Gas data reference sources		16

1 Introduction

For many years, the gas industry has produced a wide range of gas mixtures. All gas mixing operations require the normal safety procedures, practices and controls which are followed when filling standard industrial gases. Additional controls are required when mixing potentially incompatible gases. For this reason, great care is necessary during the preparation of such mixtures to ensure that no uncontrolled reactions take place.

Regulations and procedures for gas mixing vary in some details from one manufacturer to another; however, they should always be based on the same safety principles. Details concerning the safe manufacture of oxidant-fuel mixtures are described in IGC document 139/07 'Safe preparation of compressed oxidant-fuel gas mixtures in cylinders'.

Manufacturers of gas mixtures for medical use should also refer to AIGA 023/05 'Guide for Good Manufacturing Practice - Production of Medicinal Gases'.

2 Scope and Purpose

There is no intention that this Code of Practice should be a manual on how to manufacture gas mixtures. The sole aim of this Code is to set out the basic requirements to ensure that gas mixtures are manufactured safely.

3 Definitions

For the purpose of this document, the following definitions apply:

- *cylinder*: For the purposes of this document, a cylinder is defined as any transportable receptacle that can be filled with gas under pressure.
- *filling degree (filling ratio)*: The amount of a liquefied gas that can safely be filled into a cylinder without over-pressurisation of the cylinder under all anticipated ambient conditions. This term is also known as fill density or fill ratio. The filling degree (f) (prescribed in ADR, 49 CFR 173.304) is expressed as the ratio: (M/C) ,
Where: M = mass of gas filled (Kg)
C = cylinder water capacity (Litres)
- *hazop*: A technique to identify and assess potential hazards that might arise during the operation of plant or equipment. A study is normally carried out to assess the potential effects of various malfunctions of the equipment or plant (e.g. reverse flow, excessive temperature or pressure etc.).
- *hygroscopic*: A substance that has an affinity for water is said to be "hygroscopic". Many acid gases are hygroscopic (e.g. hydrogen chloride) and, when in the wet state, are normally much more reactive with materials of construction.
- *liquefied gas*: For the purposes of this document, a liquefied gas is a gas that can exist as a liquid in a cylinder with a vapour pressure in excess of atmospheric pressure at ambient temperatures. Liquefied gases are normally filled into cylinders by mass to prescribed *filling degrees*, however, where they are filled as components of a gas mixture and their liquefaction in the mixture is not expected under normal ambient conditions, they may be filled by pressure.
- *industrial gas*: A gas or gas mixture which is available on a large scale (e.g. nitrogen, oxygen etc.).
- *intermediate analysis*: An analysis carried out part-way through the process of filling a gas mixture into a cylinder (or cylinders). Such an analysis is normally carried out to confirm the concentrations (and sometimes the identities) of the components that have been filled before a subsequent component is added.
- *passivation*: For the purposes of this document, *passivation* is a procedure that is applied where there is a possibility of a reaction between a reactive gas and the container or system into which it is going to be introduced. *Passivation* ensures that any reaction takes place under controlled conditions. *Passivation* may also be used to ensure the stability of a gas mixture. *Passivation* is usually carried out using a mixture containing the reactive gas diluted in an inert gas.
- *premix*: For the purposes of this document, a premix is a gas mixture which is used as one of the supply gases during the filling of a gas mixture. The use of premixes can enable low concentration components to be filled accurately and can also eliminate any potential hazards when filling certain gas mixtures containing potentially incompatible components.

- *shall*: The use of the word “shall” in this document implies a very strong concern or instruction.
- *should*: The use of the word “should” in this document indicates a recommendation.

4 Principles of safe gas mixing

This section sets out the basic principles that shall be followed to ensure gas mixtures are produced safely.

4.1 Principle 1: written instructions shall be provided

Gas mixtures shall only be filled against written and approved instructions. Normally the instructions issued will comprise operating procedures for the plant & equipment and specific instructions for each gas mixture to be produced.

4.2 Principle 2: equipment and facilities shall be properly designed

Gas mixtures shall only be prepared in properly equipped and approved facilities where provision has been made for:-

- Adequate segregation of filling flammable and oxidant gases and other potentially incompatible components to clearly defined areas.
- Prevention of feed-back of gas from filling systems into supply gas systems.
- Safe and environmentally responsible disposal of waste gases. The IGC document ‘Disposal of gases’ gives further detailed information.

4.3 Principle 3: written instructions shall be prepared by competent staff using recognised data

Gas mixing instructions shall be prepared by trained and competent staff who checks for:

- a) Availability of recognised data.
- b) Safety of the proposed method of manufacture and the final mixture.
- c) Unsafe situations that could arise from the liquefaction (condensation) of components during and after mixing.
- d) Quantity of product versus cylinder size (particularly with respect to liquefied gas mixtures, to ensure that the cylinder is not over-filled).
- e) Tolerance requirements for safe mixing.

4.4 Principle 4: personnel shall be trained

Personnel engaged in gas mixing shall be given training based on written instructions covering:

- a) All aspects of preparing gas mixtures.
- b) The key characteristics of the gases being handled and the safety requirements when dealing with them.
- c) Protective clothing and equipment.
- d) Safety rules, emergency and first-aid procedures.

The training shall be properly recorded and up-dated regularly.

4.5 Principle 5: intended cylinder-content shall be identified before filling

Before any cylinder is filled, it shall be clearly identified with the names and respective nominal concentrations of the intended mixture components (or the mixture registered trade name where appropriate). Alternative methods of identification which give an equivalent level of safety may be used. The content and status of the container during the production process shall also be recorded.

4.6 Principle 6: supply gases and cylinders shall be controlled

There shall be adequate controls to ensure:

- a) that only the intended gases are used to prepare gas mixtures.

- b) that cylinders are suitable for the mixture, that they are properly prepared and that they are free of any contaminants which may affect the safety of the filling process and/or the intended use of the mixture.

4.7 Principle 7: facilities and procedures shall be audited

All gas mixing facilities and procedures shall be audited regularly for compliance with all the above six principles, 4.1 to 4.6.

5 Feasibility and classification of gas mixtures

There are in excess of 100 commonly available liquefied and permanent gases and a very large number of liquids whose vapours are used in the formulation of gas mixtures. Gas mixtures can contain any number of components at almost any concentration, provided they are safe and technically feasible to produce. Hence, the potential range of available gas mixtures is almost infinite. This section gives basic guidance on the types of gas mixtures produced and the constraints that may be applicable to their manufacture.

5.1 Gas mixture availability constraints

The main constraints on the availability of gas mixtures are concerned with:

- a) *Safety*: The gas industry will not manufacture any gas mixture which may compromise the integrity of the cylinder, valve, dip tube or filling system.
- b) *Technical feasibility*: The physical and chemical properties of some mixture components have a limiting effect on what can be practicably manufactured (e.g. a very low vapour pressure can limit the concentration of the component and the final filling pressure of the gas mixture).

5.2 Gas mixture categories

Generally, gas mixtures can be grouped into two broad categories:

- a) *Standard gas mixtures*: those which are filled repeatedly on a large scale. Normally these are relatively simple, containing two or three common standard gas components with filling and analytical tolerances which are not particularly critical.
- b) *Special mixtures*: those which are filled on a smaller scale than standard gas mixtures. These mixtures are frequently more complex than standard gas mixtures.

6 Gas mixing instructions

Gases and vapours may be mixed in any combinations at any concentrations provided the mixture is technically feasible and safe, i.e. components are compatible with each other and with the cylinder and its valve, both during filling and after mixing. The purpose of this section is to set out the principles and controls necessary to ensure safe gas mixing instructions can be formulated and issued. Some additional guidance is given on possible gas mixture filling strategies.

6.1 General controls

Gas mixtures shall only be filled against written and approved procedures. Such procedures shall cover both the filling equipment to be used and the specific gas mixture to be prepared.

6.2 Mixture-specific manufacturing instructions

Instructions specific to the mixture to be filled shall include:

- a) Details of the cylinder and valve and their preparation.
- b) The components and quantities to be added.
- c) The means of measuring the components into the cylinder and the filling equipment to be used.
- d) Any special constraints relating to the rate at which the components are to be added (e.g. to minimise temperature increases).
- e) The method of mixing the components.

- f) Any intermediate analysis requirements (i.e. analysis to be carried out during the filling process to confirm the correct quantities of some components have been filled before the addition of other component(s)).

6.3 Personnel responsible for preparing & authorising gas mixing instructions

Such personnel shall have sufficient technical education and relevant experience to be able to fully understand the chemical, physical and engineering principles involved in the formulation of mixing instructions and their subsequent approval. There shall be a list of authorised personnel. Gas mixing procedures shall never be compromised to meet production pressures. Such personnel shall work to formalised procedures and instructions and shall work and communicate closely with the personnel who design gas mixing facilities and who prepare, fill and analyse gas mixtures.

6.4 Safety system

The safety system shall ensure that gases are not mixed without proper written and approved mixing instructions and that the integrity of the containers being filled is not compromised. The gas mixing instruction approval system shall take into account:

- a) The enquiry and quotation stage - to ensure that no commitment is given to prepare an unsafe mixture.
- b) The acceptance of order into processing system - to ensure that orders for unsafe mixtures are not accepted.
- c) The formulation of gas mixing instructions - to ensure that formulation is only undertaken by authorised personnel.
- d) The approval of gas mixing instructions - to ensure approval of written instructions prior to issue to production (see 6.5 below).
- e) If a computer system is used to calculate and/or store gas mixing instructions – then to ensure that non-approved instructions are not released for production use. Safeguards against keying errors shall be incorporated into the system.

6.5 Approval of gas mixing instructions

Gas mixing instructions may be formulated manually or with the aid of appropriate computer software and database(s). Such software and database(s) shall be validated as correct and secure. Once formulated, gas mixing instructions may be issued directly for use and/or may be stored in a computer file for subsequent issue. Where a computer file is used for the storage and issue of previously formulated gas mixing instructions, it shall be validated as secure. All entries into the file shall be checked to ensure there are no keying errors (including checking units of component concentration and method of measurement during filling).

Gas mixing instructions, whether formulated manually or with the aid of a computer shall be checked, as follows, before issue for use or entry into a computer file for subsequent use:-

- *all instructions*: by at least one competent person (the blender can be the competent person).
- *instructions for mixtures which contain potentially incompatible components*: by at least one additional competent person. For compressed oxidant-fuel gas mixtures refer to IGC document 139/07 'Safe Preparation of compressed oxidant-fuel gas mixtures in cylinders'.

6.6 Adjustment of gas mixing instructions

The adjustment of existing gas mixing instructions shall be subject to the same rigorous controls as new instructions. They shall not be adjusted without the authorisations detailed in 6.5 above.

6.7 Adjustment of existing mixtures

When a gas mixture is found to be out of tolerance after analysis, it is sometimes practicable to adjust the composition of the mixture by addition of one or more of the mixture component gases. Before this operation is undertaken, written instructions shall be formulated. Where the mixture adjustment involves addition of a gas which is potentially incompatible with the existing mixture components, the mixture adjustment instructions shall be approved by a competent person who is accountable for safety.

6.8 Consideration of mixing methods

The methods generally available for the preparation of gas mixtures in cylinders are listed below, together with the considerations necessary for safe operation. Combinations of two or more of these methods may sometimes be used.

6.8.1 Static methods

In this method, the mixture is produced directly in the cylinder by adding measured quantities of each of the mixture components. Mixing of the components may not be instantaneous and concentration gradients can be present during and immediately after filling the cylinder. This shall be taken into account to ensure that no dangerous mixtures can exist during filling. There are three commonly used methods of measuring the quantities of mixture components into the cylinder during filling. It may be appropriate to use a combination of these methods to prepare some gas mixtures. The static methods are as follows:-

- a) *Manometric or partial pressure method:* Mixture components are filled into the cylinder to calculated pressures. The calculated pressures shall take into account the component compressibility factors and shall ensure that unwanted component liquefaction does not occur during or after the preparation of the mixture.
- b) *Volumetric method:* Calculated volumes of mixture components are filled into the cylinder. The calculated volumes shall ensure that unwanted component liquefaction does not occur during or after the preparation of the mixture.
- c) *Gravimetric method:* Calculated masses of mixture components are filled into the cylinder. The calculated masses shall ensure that unwanted component liquefaction does not occur during or after the preparation of the mixture.

6.8.2 Dynamic method

In this method the mixture is produced prior to filling into the cylinder by blending the components dynamically at calculated flow-rates. Normally, the dynamic blend is made at low pressure and subsequently compressed into the cylinder. Care shall be taken to ensure that a dangerous blend cannot be made if the flow control system fails. Account shall be taken of temperature rises during compression and the compatibility of lubricants with the mixture being compressed.

6.9 Compatibility considerations

Gas mixtures shall only be prepared where the proposed components are compatible with each other and with the cylinder and valve at the concentrations and pressures to be encountered during and after mixing.

6.9.1 Cylinders and cylinder valves

The cylinder and cylinder valve shall be suitable for their intended service.

- a) Cylinders and cylinder valves shall be suitable for the operating pressure. Due account shall be taken of the possible developed pressure at the elevated temperatures that can be encountered in storage, transport and use. This is particularly important in the case of liquefied gas mixtures. Also refer to ADR, 49CFR 173.300, 173.302, 173.304 rules governing filling degrees and filling pressures.
- b) Cylinders and cylinder valve materials (e.g. body, seat & packing) shall be chemically compatible with the gases contained. Attention is drawn to the need for expert consideration of all gas, cylinder and valve compatibility issues. Examples of potential incompatibilities and other chemical compatibility issues that should be taken into account include (not a complete list):-
 - Halogens and halogen compounds may not be compatible with aluminium cylinders. Ensure that the concentrations of halogens and halogen compounds used in the mixture are compatible with the material of the cylinders used.
 - Highly stressed steels can be susceptible to embrittlement, stress corrosion and other corrosion with certain gases such as hydrogen, ammonia, carbon monoxide, hydrogen sulphide, some halogens and halogen compounds. (see EIGA IGC 100/03 Document "Hydrogen cylinders and transport vessels").
 - Possible effect of any impurities which the gas may contain.

- Some gases may only be compatible when dry. In these cases, both the gas and the cylinder shall be free of moisture.
 - Where a gas is corrosive when wet, particularly if the gas is also hygroscopic, the valve design and material shall be such as to minimise the effect of corrosion on the valve operating mechanism. This is important, as the user may be careless about purging before and after connection and disconnection of the valve to the equipment, thus allowing atmospheric moisture into the valve outlet.
 - When changing from one gas or gas mixture service to another, cylinders shall be free of substances which may remain from previous service. Gases may normally be removed by evacuation and/or purging (in some cases, such operations are best carried out whilst baking the cylinder). Solid and liquid substances (such as possible reaction products) may require the cylinder to be taken out of service, cleaned and inspected internally prior to refilling.
 - It may be necessary to “passivate” cylinders, valves and equipment before certain highly reactive gases (e.g. fluorine) are introduced for the first time. “Passivation” is intended to minimise the risk of a violent reaction between the gas and materials that the gas comes into contact with. It is normally carried out by slowly introducing the gas to the system, initially in a diluted form and at low pressure, to ensure that any reactions that are likely to take place do so under controlled conditions.
- c) Cylinders shall be periodically inspected and tested (except non-refillable cylinders). Periods between inspection and test and the extent of the inspection and pressure to which cylinders are tested are dependant on the gas contained, the cylinder design code and the country where the cylinder is filled and/or used. Such details are normally defined in international and national regulations. Refer to ADR, 49 CFR 100-80 rules governing periodic inspection and test requirements.

6.9.2 Mixture components

When a mixture is proposed, the approved competent person shall seek evidence from published literature or in-house experimental data to establish component compatibility. Gas mixtures will normally fall into one of the following categories:-

- a) Mixtures of components that are compatible at all concentrations, pressures and temperatures that can be encountered - gas mixing instructions can be formulated and approved.
- b) Mixtures of potentially incompatible components, where the component compatibility data or evidence is available at conditions different to those to be encountered during mixing. In such cases, the data or evidence shall be interpreted and safety margins applied according to the producer's own published in-house rules. These rules shall be observed for the mixing instruction to be approved.
- c) Mixtures of potentially incompatible components where the component compatibility data or evidence is not available or shows non-compatibility. In such cases the gas mixing instruction cannot be prepared without further thorough investigation and approval. The policy for dealing with such cases should be defined in an internal company procedure.

6.9.3 Safety margins

When establishing safety margins for the mixing of potentially incompatible components, considerations shall include the following:-

- a) The availability and accuracy of data.
- b) The accuracy of control of the mixing operation.
- c) A detailed understanding of the hazards of potential reactions (e.g. explosion data, energy releases, pressure rise etc.).
- d) The possibility that, under certain conditions, condensation of one or more of the components can occur and could give rise to the formation of dangerous mixtures in the gaseous phase or at the interface with the liquid phase.

6.10 Identification and labelling

The following shall be observed:

- a) *Prior to filling*:- Cylinder shall be painted when required, clearly and durably marked with:-

- A clear indication of the gases to be contained (e.g. names, chemical formulae, nominal concentrations of components of the mixture or the mixture registered trade name where appropriate).
- An indication of the potential hazardous properties of the mixture (e.g. toxic, flammable etc.).
- For liquefied gas mixtures, the tare weight of the cylinder (including valve, dip tube, fixed valve protection etc.).
- Any other legally required markings or stampings to the cylinder or its valve.
- b) *Prior to shipping:* all cylinders shall be labelled to include:-
 - All legally required labels for conveyance to and use at the final destination.
 - The name and contact details of supplier (including emergency contact).

7 Design & operation of gas mixing facilities

All safety and legal requirements relating to the handling, storage, filling and maintenance of cylinders and filling systems for the various categories of pure gases also apply to gas mixtures. It is recommended that safety and operability risk assessments are carried out on all processes and procedures. This section sets out basic guidance and identifies some of the key issues for consideration. Where hazards are identified which could be fatal or lead to very serious injury, the system shall be designed to eliminate these hazards. Where elimination of the hazard is not possible, the system shall be designed to incorporate physical controls to reduce the risks to a practicable minimum. Reliance on the operator following a procedure shall be used where there is no feasible alternative, but key stages in the procedure shall be subjected to independent checking by another individual. Change management procedures shall be used to ensure changes in operational procedures are reviewed and risk assessed prior to implementation.

7.1 General requirements

Issues for consideration include the following (not an exhaustive list):-

- a) *Operating & storage areas*
 - The ventilation requirements.
 - The segregation of filling areas.
 - The provision of adequate emergency exits.
 - The controlled access of personnel.
 - Fire protection and fire fighting equipment.
 - The exclusion of ignition sources and protection against electrostatic discharge where flammable gases are handled.
 - The gas monitoring where toxic, flammable gases or oxygen-enriched or depleted atmospheres are a potential hazard.
- b) *Equipment*
 - The suitability of equipment, materials of construction and pressure rating.
 - The gas disposal systems.
 - The accuracy of all measuring and analytical equipment used in the preparation of gas mixtures - shall be adequate for the purpose and documented.
 - Drawings and labelling. Note: It may be required to expand to include manuals/procedures, etc.
- c) *Supply gases*
 - Separate inert gas supplies for flammable-inert gas mixtures and for oxygen-inert gas mixtures should be considered to prevent the accidental production of oxidant-fuel mixtures.
 - Adequate labelling on all gas supply pipelines and cylinders.
 - The storage identification and stock rotation for supply cylinders.
 - Confidence in the supply gas certification and freedom from potentially hazardous impurities (including *premixes*).
- d) *Control of cylinders*
 - The safe handling of cylinders - techniques, equipment and routing.
 - A means of securing free standing cylinders against falling where necessary.
 - The control of cylinders in the mixture filling areas (i.e. kept to a minimum).
 - Ensuring that polymerisable substances (such as ethylene oxide and 1,3-butadiene) are stored, checked periodically and used in accordance with the supplier's instructions.
 - The provision of leak testing full cylinders and filling systems.

- Correct labelling.
- The adequate provision of storage areas suitable for the hazard class or gases to be manufactured.

7.2 Specific requirements

In addition to the general requirements of 7.1, the following are given for guidance when designing and operating facilities associated with gas mixtures:

7.2.1 Incoming cylinder reception & inspection

Operators of gas mixing facilities should recognise the relative complexity which results from the multiplicity of gas mixture combinations. Cylinders shall be identified and segregated for subsequent residual gas disposal and cylinder maintenance (where appropriate). Adequate space for this activity shall be allocated.

7.2.2 Disposal of residual gases

Adequate facilities shall be available for the safe disposal or recovery of all residual gases likely to be encountered from both the gas mixing process and from cylinders returned by customers after use. Typical guidance concerning the provision of such facilities is given in IGC Document 30/07 'Disposal of Gases'. Facilities established for the manufacture of gas mixtures frequently handle a large range of mixture components. Gas disposal and gas recovery equipment can tend to be expensive, hence one installation may be designed to handle a multiplicity of gases and gas mixtures. It is therefore very important to have adequate controls in place to prevent the inadvertent mixing (in potentially hazardous concentrations) of inter-reactive gases or other materials in the gas disposal equipment. Examples where controls are needed include:-

- a) To ensure that the contents of all cylinders assigned for disposal have been correctly identified.
- b) To ensure that there is no risk of mixing incompatible gases, such as flammable and oxidant gases, within the gas disposal equipment which could give rise to an uncontrolled reaction.
- c) To ensure that there are no violent reactions in the event of it being necessary to pass hydride gases (particularly if they are mixed with other flammable gases) into oxidant chemicals as this could give rise to a violent reaction and possibly an explosion.
- d) To ensure that, where it is necessary to use the same scrubbing liquor for certain oxidants and acids, changes in the scrubbing chemical pH are avoided (this could result in the release of toxic gas from the chemical).
- e) To ensure there are qualified, competent and appropriately equipped personnel available to specify or carry out certain "non-routine" gas disposal operations. Examples of typical "non-routine" gas disposal operations include:-
 - Where there is no suitable gas disposal equipment readily available. Such operations shall be assessed by a person who has appropriate chemical experience and who is able to make recommendations concerning the safe gas disposal method and the equipment that can be used.
 - Where the content of the cylinder is unknown, possibly old and lacking in markings (see IGC Document 30/07 "Disposal of Gases").
 - Where the cylinder content can be potentially explosive, possibly as a result of back-feeding an incompatible material into the cylinder.
- f) Where in-house resources and facilities are not available, to ensure that cylinders are properly consigned to a licensed competent third party for gas disposal (provided the cylinders are in a safe condition for handling and transport).

7.2.3 Cylinder maintenance & preparation

In addition to the facilities that are normally required for the maintenance and preparation of cylinders for pure gases (such as those used for industrial gases) the following are likely to be required:-

- a) Facilities for a wide range of cylinder painting and labelling.
- b) Additional specialised cylinder internal inspection and cleaning equipment.
- c) Facilities for the storage and fitting of a wide range of cylinder valves.
- d) Additional and specialised cylinder internal drying equipment.

7.2.4 Design of gas mixing facilities

Gas mixing systems shall be designed by competent personnel with the relevant experience and knowledge to ensure that the systems are safe and effective. New cylinder filling manifold designs or modifications shall be reviewed and approved prior to the use of the system. Wherever possible the systems should be simple to operate with a logical layout of cylinder filling manifold to minimise potential operator errors. Key points for consideration in the design of the gas mixing facility include :-

- a) Gas filling systems and filling areas should be segregated as far as is practicable to eliminate the risk of inadvertently mixing of incompatible gases.
- b) Appendix 1 gives reference sources of physical, chemical, flammability and oxidising properties for gas mixture components and can be used in conjunction with the appropriate SDS data to assess the compatibility of products.
- c) Where incompatible gases are being mixed, the provision of a designated system combined with strict operational controls is necessary. There shall be sufficient checks to ensure that the mixture components are correctly added (as specified on the gas mixing instruction). This is to ensure that there is no risk of a hazardous condition inside the cylinder being filled at any time during the filling process.
- d) Where flammable components are to be stored and filled, consideration shall be given to the following:-
 - The electrical classification of equipment (voltages, flame proofing etc.).
 - The earthing of cylinder filling manifolds and associated equipment.
 - The sources of static discharge.
 - The building ventilation.
 - Flammable gas detection systems and alarms.
 - Explosion relief of buildings.
- e) Where toxic components are to be stored and filled consideration shall be given to the following:-
 - Toxic gas detection systems and alarms
 - Personal detectors, availability of PPE
 - Building ventilation.
- f) Vent lines from cylinder filling manifolds shall be installed to let any residual gas be vented in a safe manner. Care shall be taken to ensure that vent lines are installed in a manner to avoid any reaction between incompatible products. The vent lines should be separated and have the facility to purge the lines with inert gas.
- g) Precautions should be taken to avoid the suck back of contaminants (oil, scrubber solutions etc.) from vacuum systems into cylinder filling manifolds and cylinders. Vacuum pumps used in oxidant service should use an appropriate oxidant compatible lubricant. (e.g. fluorinated pump oils).
- h) Adequate provision shall be made to prevent back-feeding of partially filled cylinders into other filling systems or cylinders via supply, vent and vacuum systems. This is particularly important where a common supply feeds different category filling areas.
- i) The interconnection of incompatible supply gases shall not be possible through the various cylinder filling manifolds and mixing systems. Non return valves and block valves shall not be relied on as the only means of protection against interconnection of incompatible gases.
- j) Connections to the cylinder filling manifold system should be designed to avoid the possibility of connection of unauthorised products. (i.e. exclusion of oxidants from cylinder filling manifolds to be used exclusively for flammable gases).
- k) Temperature sensitive components (e.g. plastic gaskets) should be avoided where there is a risk of high temperatures occurring. The systems should be designed to avoid the risks associated with adiabatic compression of gases.
- l) Pressure sensing devices and other cylinder filling manifold equipment shall be selected to ensure that they give meaningful indications to the operator and are pressure rated for the system. It may be desirable to fit over-pressure protecting devices to low pressure, pressure sensing devices that are incorporated in high pressure systems, however, such devices may not always work, so it is advisable to also fit gauge isolating valves.
- m) Provision should be made for "parking" positions for cylinder filling hoses, so that dirt and atmospheric contamination is excluded when the hoses are not in use.
- n) There should be adequate labelling to identify valves and other operating controls and equipment.
- o) The number and size of cylinders permitted to be filled on the system should be defined and easily accessible to the operator. For automated gravimetric fill systems both the pressure and mass measurements are vital to ensure that the cylinders cannot be overfilled if wrong cylinder is connected.

7.2.5 Operation of gas mixture filling facilities

In addition to the provision of equipment operating instructions and gas mixture filling instructions (recipes), the following safeguards shall be in place:-

- a) Checks to be made by the fill operator to ensure that the cylinder and valve are in good condition and within the re-inspection period.
- b) Checks to be made by the fill operator to verify the pressure rating of the cylinder and where appropriate perform a tare check of the cylinder to verify cylinder is empty.
- c) There shall be adequate segregation of cylinder supply gases (i.e. pure products and premixes).
- d) Pure products and premixes shall be clearly identified with all relevant markings and current composition information of the contents in the appropriate language for the operator.
- e) Piped gas supply lines shall be adequately purged prior to use to avoid incompatible reactions and potential contamination issues.
- f) Cylinder valve outlet adapters should be controlled in line with the level of risk in the event of their incorrect or mistaken use. Adapters which enable inter-connection of incompatible gases should not be readily available in the gas mixing area – such adapters shall be closely controlled (e.g. kept in a secure place and only issued for specific purposes).
- g) Where gas mixtures are prepared by non- dynamic methods, provision shall be made for homogenising the gas mixtures during or after filling where this is required by the mixing instructions. Cylinder rolling and/or the fitting of dip tubes within cylinders are mixing methods commonly employed.
- h) Analysis of the intermediate mixture can be used to verify the composition of the mixture prior to adding the incompatible components.

7.2.6 Gas analysis

The following brief notes are given for guidance:-

- a) Gas analysis facilities should be provided to fulfil the following functions:-
 - Identify and verify the quality of the gas mixture components.
 - Verify the composition of the final gas mixture and any intermediate mixtures as required by the gas mixing instructions.
 - Identify the composition of gases and gas mixtures in returned cylinders.
- b) Commonly available gas analysis equipment of the type which is required to analyse the multiplicity of gas mixtures and their trace impurities is not normally of certified 'flameproof' construction and often does not lend itself to inert gas purging. This shall be recognised when specifying the siting of equipment, its environment and the construction of sampling systems.
- c) It is recommended when analysing flammable and or toxic gases and mixtures to provide environmental monitoring equipment and or to provide additional localised ventilation.
- d) Proper arrangements shall be made for the safe disposal of gas samples.
- e) Where analysis equipment is used with incompatible gases purging facilities shall be installed for the sampling and analysis systems.

8 Personnel training

Personnel involved in the handling of cylinders and the mixing of gases shall be trained to an appropriate level which is commensurate with their degree of involvement. A formal training programme shall be undertaken against all relevant written operating procedures, recorded and regularly updated. Personnel who carry out safety-critical activities (e.g. the manufacture of flammable plus oxidant gas mixtures) shall undergo formal competence checks to ensure they have a complete understanding of the processes, topics and other material on which they have been trained. Competence checks shall be recorded and signed by both trainer and trainee. Also, for certain safety-critical activities it may be advisable to consider to perform psychological screening checks and/or unscheduled personnel screening programs for drugs, alcohol etc. This section sets out some of the training topics for consideration.

8.1 All personnel

Regular training reviews should be conducted to review ongoing training needs of all personnel. In addition all relevant personnel shall be made aware of the hazards of any new products and/or changes to operating procedures and systems. A policy shall be established to define the activities for

which the understanding and competence of individuals shall be periodically re-assessed and with what frequency. Personnel meeting the requirements of the competence checks would then be authorised to perform the tasks against which they have been checked. In addition to specific job training, some of the following training topics shall be considered:-

- a) The site safety rules and company's safety policy.
- b) The emergency and site evacuation procedures.
- c) The use of personal protective equipment.
- d) Awareness of 'permit to work' system, if no detailed SOP is available.
- e) The identification of cylinder contents.
- f) The basic physical, chemical and hazardous properties of gases handled.
- g) The safe handling and storage of cylinders.
- h) The different sizes, types etc. of cylinders.
- i) The different cylinder valve types, valve outlets and applications.

8.2 Cylinder reception/receiving personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) The recognition of cylinders received in a potentially hazardous condition and the immediate action to be taken.
- b) Cylinder retest date requirements.

8.3 Gas disposal personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) A detailed understanding of the physical, chemical and hazardous properties of the gases and disposal reagents and materials being handled.
- b) The key safety rules (including seeking expert advice on cylinders with unknown contents or of unknown origin or with inoperable valves. Ensuring cylinders are made safe and appropriately labelled before being sent to the cylinder maintenance workshop).
- c) The safe and environmentally responsible disposal of waste gases and operation of waste gas disposal equipment (written procedures to be provided).
(see also IGC Document "Disposal of Gases").

8.4 Cylinder maintenance personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) The cylinder maintenance and test rules and regulations.
- b) An understanding of different types of cylinders, their identification and markings and their applications.
- c) An understanding of different types of cylinder valves and their applications.
- d) The safety rules for cylinder maintenance (such as ensuring cylinders are de-pressurised and freed from hazardous gases before valve removal).
- e) The rejection criteria for unsuitable cylinders and rejection of cylinders of unknown origin.
- f) The procedures to scrap unserviceable cylinders.
- g) Cylinder painting requirements.
- h) The safe operation of cylinder maintenance plant (written procedures shall be provided).

8.5 Cylinder filling personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) A detailed understanding of the physical, chemical and hazardous properties of the gases and materials being handled.
- b) Personnel involved in the mixing of flammable plus oxidant or other potentially reactive mixtures should have previous experience in other gas mixture filling and receive additional training on the specialised requirements of producing these mixtures.
- c) Key safety rules. Examples include:-

- That no gases are to be mixed without written instructions.
- That no cylinders are to be filled unless they are in good condition, correctly supplied, correctly labelled for their intended contents and within statutory the test period.
- The rejection of unsuitable cylinders, including cylinders of unknown origin.
- d) The operation of gas mixing equipment (written procedures shall be provided).
- e) Checks during and after cylinder filling (including: correct cylinder, valve operation, leak checks and fitting of valve outlet cap nuts or plugs where appropriate).
- f) The safe disposal of waste gases and operation of waste gas disposal equipment (written procedures shall be provided).

8.6 Gas analysis personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) A detailed understanding of the physical, chemical and hazardous properties of gases and materials being handled.
- b) Operation of gas analysis equipment (written procedures to be provided).
- c) Awareness of product specifications.
- d) Checks during and after gas analysis (including correct cylinder valve operations, leak checks and fitting valve outlet cap nuts or plugs where appropriate. Fitting valve protection covers).

8.7 Cylinder shipping personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) Ensuring that the cylinder valve is firmly closed and valve outlet plug or cap nut fitted where appropriate.
- b) Ensuring that the valve protection cover is properly fitted.
- c) Ensuring that cylinders are properly labelled with their contents (including the fixture of the appropriate hazard warning labels required for transport).
- d) Ensuring that the cylinders are properly labelled for their final destination and that transport and shipping documents are correct.

8.8 Plant maintenance personnel

In addition to 8.1 above and specific job training, training topics to be considered should include the following:-

- a) An understanding of physical, chemical and hazardous properties of the gases and materials being handled.
- b) The company's planned maintenance policy (where appropriate).
- c) The necessary fitting, welding and electrical, etc. skills.
- d) The provision of equipment drawings, maintenance procedures, etc.
- e) The key safety rules. This includes:-
 - 'Permit to work' system (where applicable).
 - Not to start maintenance work until the plant and area are declared to be safe by a competent person.
 - The labelling of equipment to ensure it remains safe whilst maintenance work is in progress.
 - Special personal protective measures.
- f) The disposal arrangements for potentially contaminated waste materials (e.g. oils, solvents etc.).

8.9 Personnel engaged in preparing operating procedures and gas mixing instructions

Personnel who prepare and check operating procedures and gas mixing instructions shall be technically competent, experienced in the gas business and able to prepare concise and easily understood written instructions. They shall have received training in their company's requirements with respect to the style of the instructions they prepare. Personnel engaged in preparing gas mixing instructions, in addition to having practical experience of gas mixing operations, shall have a proven knowledge of and access to the physical, chemical and hazardous properties of the gases being handled. They shall also have the necessary mathematical and computer skills (where computers are

used) to carry out the appropriate calculations. They should also communicate regularly with cylinder filling personnel. Additional training requirements include:-

- a) A good knowledge of applicable legislation.
- b) The company system which authorises changes to equipment and procedures.
- c) The assessment of material compatibility.
- d) The identification of potential hazards and material compatibility issues for products not previously handled.

8.10 Personnel engaged in plant and equipment design

Personnel who design plant and equipment shall be technically competent and fully understand the physical, chemical and hazardous properties of the gases being handled. Normally such personnel will possess a recognised qualification in an appropriate engineering subject (e.g. chemical or mechanical or electrical engineering). They shall have the necessary skills to carry out appropriate design calculations and check specifications of bought-in-plant and equipment (e.g. material compatibility, pressure ratings etc.). They shall have the necessary skills to ensure that the plant they design incorporates all the necessary safety features to ensure safe operation. Often, such personnel need to be able to oversee the installation and testing of plant and equipment to ensure the work is carried out to the required standards.

8.11 Other personnel

Certain personnel in direct contact with customers and gas users, such as sales and marketing staff may need a basic understanding of the specific safety requirements related to the mixing of gases to ensure they refer certain gas mixtures to technical personnel before a commitment is made to produce. It may also be helpful if they have a basic understanding of the safe handling of cylinders to enable them to respond correctly to simple customer enquiries.

8.12 First-aid training

There shall be an adequate number of personnel trained to carry out first aid in the event of personal injury at work. Where toxic or corrosive gases are handled, access to specially trained first aid and medical personnel should be available. Such personnel shall be aware of the special properties of the substances being handled, have the necessary first aid requisites readily available and be qualified to administer them.

9 Safety

All normal requirements for the safe handling, storage, filling and maintenance of cylinders and filling systems for pure gases (such as industrial gases) also apply to gas mixtures. This section identifies some of the issues for consideration.

9.1 Provision of personal protective equipment

Protective equipment to be considered includes the following:-

- a) *When handling cylinders:* e.g. safety foot-ware; heavy duty gloves; safety eye protection.
- b) *To help to avoid ignition sources:* anti-static soles on foot-ware (e.g. not rubber); anti-static protective clothing (e.g. not nylon); anti-spark tools (e.g. bronze). *To identify gas leaks:* toxic gas monitor; oxygen depletion and enrichment monitor; flammable gas monitor (e.g. when carrying out maintenance work). Atmospheric monitors shall be calibrated and checked regularly in accordance with the manufacturer's instructions.
- c) *For protection against gas leaks:* breathing apparatus (normally the type that supplies a positive air pressure to the face mask). Breathing equipment shall be regularly cleaned and checked to ensure correct operation and that the air cylinders are fully charged. Such maintenance shall be carried out each time the equipment is used by personnel competent to do this work.
- d) *When handling corrosive chemicals:* face shield; chemically resistant gauntlets; chemically resistant apron or overalls; chemically resistant boots.
- e) *For emergency use:* fire extinguishers, self contained positive pressure breathing equipment; face shield; emergency shower, chemically resistant gauntlets; complete body protection suit (e.g. for entering area contaminated with corrosive gas).

- f) *First aid equipment*: this should include access to the specialised requisites for immediate administration, where there is a risk of exposure to those gases and liquids that may require such treatment (e.g. cyanides, HF, F₂, ClF₃, certain hydrides - consult the SDS of the products being handled).
- g) *All equipment*: All personal protective equipment shall be inspected regularly. It shall be kept in good functional condition. It should be kept in a designated storage area ready for immediate use.

9.2 Safety rules

The fundamental safety rules which apply to the gas mixing facility shall be documented, form part of the employees' training requirements and shall be rigorously enforced. Safety rules are likely to include requirements for the following:-

- a) Personnel training in the duties that they have to carry out.
- b) Personal protective equipment.
- c) No smoking areas and areas where smoking materials and other potential ignition sources are forbidden. Consideration should also be given to restricting the use of portable electrical appliances in such areas (e.g. mobile telephones).
- d) "Permit-to-work" system, particularly with respect to maintenance work in potentially hazardous areas.
- e) Site emergency procedures including evacuation, individual's responsibilities and location and use of emergency equipment.

9.3 Emergency planning

There should be published emergency response plans which are regularly practised. These plans shall have a primary regard for the safety of personnel and should take account of response requirements out-of-normal working hours. Key points for consideration when formulating emergency response plans include the following:-

- a) Legal requirements.
- b) Provision of alarm systems.
- c) Action lists and procedures for personnel in the event of an emergency (e.g. for safe emergency shut-down of equipment and processes).
- d) Plans for site evacuation, roll calls and search for unaccounted personnel and their possible rescue.
- e) Site emergency response team, including individual's responsibilities, means of communication and back-up.
- f) Provision of emergency equipment (this could include positive pressure breathing equipment, specialised protective clothing, fire fighting equipment, first aid equipment, emergency communication equipment, tools and other requisites for sealing leaking cylinders and valves, provision of a cylinder recovery vessel when necessary).
- g) Emergency power supplies (e.g. for emergency lighting).
- h) Consultation and communication with the public emergency services (e.g. fire brigade, ambulance, police, local hospital etc.).
- i) Evaluation of risks and procedures to deal with specific foreseeable scenarios, e.g. toxic gas release; liquid releases and how to avoid their entry into drains and water courses; cryogenic gas releases; oxidant-rich atmospheres; filling-hose fire; burst-disc rupture; oxygen ignitions; how to deal with "suspect unstable" cylinders etc.
- j) Consultation and communication with neighbours.
- k) Communication with the media (who should do this and what training do they need).
- l) Provision, location, regular checks and appropriate personnel training in the use of emergency equipment (e.g. fire fighting equipment, first aid requisites, breathing apparatus and special protective clothing).
- m) Provision of site plans showing the location of hazardous materials and emergency equipment.
- n) Provision of data on all products and cylinders and cylinder valves.
- o) Procedure for advising personnel that areas are safe for re-entry and re-instatement of emergency equipment.
(see also IGC Document 60/04 "Prevention of major accidents").

9.4 Audits

Regular audits of the gas mixing facility should be carried out by a competent person who is familiar with the operational and safety requirements. Audit techniques vary, however, it is recommended that audits should be recorded, together with any action points, and should include the following (not an exhaustive list):-

- a) Are written instructions provided? (see 4.1 above).
- b) Are change management procedures being followed? (see 7.0)
- c) Are equipment and facilities properly designed and approved? (see 4.2 above).
- d) Are there adequate safeguards to prevent feed-back of gases into the supply systems? (see 4.2 above).
- e) Are waste gases being safely disposed? (see 4.2 above).
- f) Are written instructions prepared by competent personnel? (see 4.3 above).
- g) Are compatibility data available for the gas mixture components both with each other and with the cylinder valve? (see 4.3 above).
- h) Are margins of safety documented for formulating mixing instructions for potentially incompatible gases such as oxidants and flammables? (see 4.3 above).
- i) Is there a safety approval system in operation for gas mixing instructions for mixtures containing potentially incompatible components, toxic gases and highly reactive gases? (see 4.3 above).
- j) Are the controls on mixture adjustment understood? (see 6.6 & 6.7 above).
- k) Is there a programme of planned and recorded training in operation? (see 4.4 above).
- l) Are cylinders marked with their intended contents prior to filling? (see 4.5 above).
- m) Are there controls to ensure that only intended supply gases are used? (see 4.6 above).
- n) Are there controls to ensure that only suitable cylinders are used, which are properly prepared and freed from contaminants? (see 4.6 above).
- o) Are all operations covered by written operating instructions and personnel training records kept up-to-date? (see 4.4 above).
- p) From a check on a representative sample of plant operating procedures, is it clear that procedures are being followed correctly? (See 4.1 & 7.2.5)
- q) Were employees interviewed familiar with the site safety rules and emergency procedures? (See 9.2 & 9.3)
- r) Is there a control procedure for modification to plant, equipment and procedures and is it being followed? (See 7)
- s) Is there a safe system for gas disposal and is it being followed and checked periodically? (See 7.2.2)
- t) Are there systems for prevention of feed-back of gases into cylinders and are they being checked periodically? (See 7.2.2)
- u) Is there evidence that plant maintenance is being carried out in accordance with company requirements? (See 7.2.2)
- v) Is there evidence that the "permit-to-work" system is operating correctly? (See 8.8)
- w) Is there evidence that safety and emergency equipment is regularly inspected and maintained and kept in the correct location? (See 9.3)
- x) Is there evidence that gas monitoring equipment is regularly checked and calibrated and in working order? (See 7.1 a)
- y) Can it be verified that safety checks are carried out on cylinders after filling and analysis (e.g. leak-tests, fitting of valve outlet cap-nuts or plugs for toxic gases etc.)? (See 8.5 c)
- z) Are cylinders stored safely in the correct locations? (See 7.1 d)
- aa) During the audit, observation of operators should be made in order to record any unsafe practices or failure to wear and use personal protective equipment as required by company safety rules.

Appendix A: Gas data reference sources

A1.1 Chemical data sources

- a) Encyclopedie des Gaz / Encyclopaedia of Gases (L'Air Liquide, Ed.), Amsterdam: Elsevier 1976
- b) CRC Handbook of Chemistry and Physics, 85th Ed., Cleveland: CRC-Press 2004
- c) Yaws, Carl L., Matheson Gas Data Book, 7. Ed., McGraw-Hill: Matheson Gas Products 2001
- d) Perry's Chemical Engineers' Handbook, 7. Ed. (Perry, R. H. et al., Ed.), New York: McGraw-Hill 1997
- e) Flammability Characteristics of Combustible Gases and Vapours - Michael Zabetakis, US Bureau of Mines, Pittsburgh, PA. May 1964.

A1.2 Standards & normative references

- a) Gases and Gas Mixtures - Determination of Fire Potential and Oxidising Ability for the selection of cylinder valve outlets, ISO 10156 (1996 - 02)
- b) Gasförmige Brennstoffe und sonstige Gase; Dichte und relative Dichte, bezogen auf den Normzustand, DIN 1871 (1980 - 05; Entwurf 1997 - 04)
- c) Determination of toxicity of a gas or gas mixture, ISO10298 (1995 –12)
- d) Determination of tissue corrosiveness of a gas or gas mixture, ISO 13338 (1995 – 11)

A1.3 EIGA publications

- a) Disposal of Gases - (IGC Doc 30/07), Brussels: IGC 2007
- b) The safe preparation of compressed oxidant-fuel gas mixtures in cylinders" (IGC Doc 139/07), Brussels: IGC 2006
- c) Hydrogen cylinders and transport vessels (IGC Doc 100/03), Brussels: IGC 2003
- d) Prevention of major accidents (IGC Doc 60/04), Brussels: IGC 2004

A1.4 Other references

- a) Sax, N. I. and Lewis, R. J., Dangerous Properties of Industrial Materials, 10. Ed., John Wiley & Sons 2000
- b) Handbook of Compressed Gases, 4. Ed. (Compressed Gas Association, Ed.), New York: van Nostrand 1999.
- c) Les Mélanges Explosifs, Paris: Institut National de Recherche et de Sécurité 1989
- d) Limit of Flammability of Gases and Vapours (Coward, H. F., Jones, G. W., Ed.); Washington: US Government Printing Office 1952.
- e) Nabert, K. and Schön, G., Sicherheitstechnische Kennzahlen brennbarer Gase und Dämpfe: Zusammengestellt aus Schrifttum und eigenen Messungen, 2 Vol., Braunschweig: Deutscher Eichverlag 1963-1990
- f) Taschenbuch für Chemiker und Physiker, 3 Vol., (d'Ans-Lax), Berlin: Springer 1970-1992.