



USE OF RESIDUAL PRESSURE VALVES

AIGA 063/14

Revision of AIGA 063/09

Asia Industrial Gases Association

3 HarbourFront Place, #09-04 HarbourFront Tower 2, Singapore 099254
Tel : +65 6276 0160 • Fax : +65 6274 9379
Internet : <http://www.asiaiga.org>



USE OF RESIDUAL PRESSURE VALVES

Disclaimer

All publications of AIGA or bearing AIGA's name contain information, including Codes of Practice, safety procedures and other technical information that were obtained from sources believed by AIGA to be reliable and/ or based on technical information and experience currently available from members of AIGA and others at the date of the publication. As such, we do not make any representation or warranty nor accept any liability as to the accuracy, completeness or correctness of the information contained in these publications.

While AIGA recommends that its members refer to or use its publications, such reference to or use thereof by its members or third parties is purely voluntary and not binding.

AIGA or its members make no guarantee of the results and assume no liability or responsibility in connection with the reference to or use of information or suggestions contained in AIGA's publications.

AIGA has no control whatsoever as regards, performance or non performance, misinterpretation, proper or improper use of any information or suggestions contained in AIGA's publications by any person or entity (including AIGA members) and AIGA expressly disclaims any liability in connection thereto.

AIGA's publications are subject to periodic review and users are cautioned to obtain the latest edition.

Table of Contents

1	Introduction	1
2	Scope and purpose	1
2.1	Scope.....	1
2.2	Purpose	1
3	Definitions	1
3.1	Residual Pressure Valve Type A (RPV Type A)	1
3.2	Residual Pressure Valve Type B (RPV Type B)	1
4	Residual Pressure Valve.....	2
4.1	Selection and design	2
4.2	Use.....	2
4.3	Fitting	2
4.4	Filling of cylinders with residual pressure valves.....	2
4.5	Removal of residual pressure valves from cylinders	2
5	Customer information.....	3

1 Introduction

Cylinder valves that retain a small positive pressure in a nominally empty gas cylinder have been available for many years.

Since the second half of the 1990s such valves have improved in reliability and the gases industry has adopted their use in large numbers.

The most important benefit of this type of valve is avoiding moisture ingress and preventing the possibility of back contamination. This improves the protection of the cylinder internally, avoiding corrosion and cylinder failure.

Additional benefits include improving the cylinder fill operation, maintaining a high gas quality and reducing internal cylinder maintenance.

The introduction of Directives like the GMP for medical gases and the Directive for food gases has increased the necessity for the use of Residual Pressure Valves (RPV).

2 Scope and purpose

2.1 Scope

This document is intended for use by gas industry members and customers and provides guidelines for the use of Residual Pressure Valves (RPV) and gives definitions for the different principles. This document does not describe any type test or retest procedures.

2.2 Purpose

The purpose of this document is to give guidance on the selection, installation and operation of these valves, such that common practices are established across the gas industry, so that these valves are of benefit to both the user and operator of gas cylinders.

3 Definitions

There are currently two main types (A or B) of Residual Pressure Valves.

Use of either Type A or Type B is dependent upon operational and gas quality requirements.

3.1 Residual Pressure Valve Type A (RPV Type A)

Type A only leaves a small positive or residual pressure in the cylinder.

3.2 Residual Pressure Valve Type B (RPV Type B)

The Type B is the valve concept, which not only leaves a small positive pressure, but it also incorporates a non-return valve to prevent back-flow of fluids into the cylinder from a higher pressure source.

Type B requires either a special filling connector or a manual adjustment to overcome the non-return valve for filling, whereas Type A usually only requires the filling pressure in the manifold to fill the cylinder. Type A - RPVs are not able to be vacuumed unless a special filling connector is used.

One difficulty of the operation of the Residual Pressure Valve is the fact that the special cylinder filling connectors may vary between manufacturers of such valves. The result of this is that there is no guarantee that an RPV from one manufacturer will be able to be filled through a filling connector from another manufacturer.

EIGA has harmonised the opening mechanism of RPV valves with non return function, having an outlet connection in accordance with ISO 5145 and designed for a working pressure > 250 bar. This allows a unified design of special filling connector to be used for valves made to this EIGA harmonized specification (see EIGA Doc 908/02). For pressures < 250 bar the various valve outlets used in different countries make this harmonisation impossible.

The other difficulty is to ensure that the special filling connectors are compatible with both kinds of valves i.e. conventional valves and those incorporating Type B RPV technology, where gas companies use both valve types in the same traffic.

Care shall be taken if mixed populations of cylinders with both RPV and conventional valve are filled together on the same manifold, as this can result in the transfer of potentially impure gas from those cylinders fitted with conventional valves to those that are protected in use by an RPV. One measure that could be taken to avoid such a contamination is to vent cylinders without RPV before connecting to the manifold.

4 Residual Pressure Valve

4.1 Selection and design

Valves, incorporating a Residual Pressure Device shall be designed, constructed and tested in accordance with EN ISO 10297 - Gas Cylinder Valves - Specification and Type Testing together with the additional requirements of ISO 15996 -- Gas Cylinder – Residual pressure valves – General requirements and Type Testing.

They are produced in accordance with EN/ISO 14246 - Gas Cylinder Valves - Manufacturing and Batch Tests.

4.2 Use

Whenever there is the possibility of internal corrosion, e.g. with steel cylinders due to ingress of a fluid, industry has in the past, developed different methods to avoid such corrosion. One possibility is the fitting of RPVs in such gas service, e.g. marine service, beverage dispense etc. In this case the Type B type with non return function is more useful.

RPVs are also used for other applications, e.g. for gas quality reasons - high purity argon or for medical or food gas products.

4.3 Fitting

Valves incorporating Residual Pressure devices shall be fitted in accordance with established operating procedures for valve fitting, (see EN ISO 13341). In all cases, immediately prior to any cylinder valve being fitted, an internal inspection of the cylinder shall be carried out to ensure that the cylinder is in good condition and free of all visible moisture.

4.4 Filling of cylinders with residual pressure valves

The filling of cylinders fitted with Residual Pressure Valves should be no different from that of filling cylinders with conventional valves. However as part of the pre-fill procedure, a check should be made on the functionality of the Residual Pressure device. This may take a number of ways depending upon the type of the Residual Pressure Valve. In the case of a Type B Residual Pressure Valve the use of a specific filling connector is sometimes necessary.

The functionality of the RPV device of every valve shall be checked. Any cylinder fitted with a RPV that does not have any pressure in the cylinder at the time of the pre-fill inspection shall be isolated and investigated to ensure that the cylinder has not been contaminated.

Note: The above does not apply to cylinders which have been fitted with RPV valves but have not yet been filled with gas

4.5 Removal of residual pressure valves from cylinders

As for all devalving operations care needs to be taken to ensure that the cylinder contains no pressure. With the removal of Residual Pressure Valves from cylinders, an additional verification is

required to ensure that the cylinder does not contain retained pressure and that the RPV device has not been jammed which may lead the operator to believe that a cylinder under pressure is empty. The use of a special device is normally required for complete depressurisation of such cylinder and to ensure that the gas passage through the valve is not blocked.

5 Customer information

Gas suppliers should consider whether or not they wish to advise users of this different type of valve. There have been occurrences reported of customers interfering/tampering with the Residual Pressure Valve mechanism.